

TABLE OF CONTENTS

TITLE PAGE	i
EXECUTIVE SUMMARY	ii
PAPERS AND REPORTS PUBLISHED	xv
TABLE OF CONTENTS	xx
ACKNOWLEDGEMENTS	xxii
1 BACKGROUND TO RESEARCH PROJECTS	1.1
1.1 The effect of bulking on the activated sludge system	1.1
1.2 Specific control of low F/M filament bulking	1.3
1.3 The selector effect on low F/M filament bulking	1.4
1.4 The AA filaments bulking hypothesis	1.5
1.5 Experimental evidence supporting the hypothesis	1.7
1.5.1 Demonstration of inhibition	1.7
1.5.2 Effect of RBCOD on OUR inhibition by NO	1.7
1.5.3 Determination of the extent of nitrate reduction and denitrification under anoxic conditions by filaments and floc-formers	1.9
1.5.4 The effect of incomplete denitrification on sludge settleability in MUCT systems	1.9
1.6 Full scale plant support for the new hypothesis	1.11
1.7 Microbiological support for the new hypothesis	1.12
1.8 Objectives of the two research projects	1.12
1.8.1 Full scale demonstration of filamentous bulking control at a biological nutrient removal activated sludge plant (Mitchells Plain Wastewater Treatment Works, Cape, South Africa)	1.13
1.8.2 AA filament bulking control with redox potential	1.13
1.9 References	1.14
2 FULL SCALE DEMONSTRATION OF FILAMENTOUS BULKING CONTROL: SUMMARY OF DETAILED REPORT <i>Hercules et al. (2002)</i>	2.1
2.1 Motivation	2.1
2.2 Research objectives	2.2
2.3 Research approach	2.2
2.4 Layout and redesign of the pilot plants at the Mitchells Plain WWTP	2.3
2.4.1 Primary settling tank (PST)	2.3
2.4.2 Biological reactors	2.3
2.4.3 Secondary settling tanks	2.6
2.5 Influent wastewater characteristics	2.7
2.5.1 Estimated influent diurnal concentrations	2.7
2.5.2 Estimated influent COD, TKN and Total P fractions	2.8
2.6 Pilot plant treatment capacity and system operating parameters	2.8
2.6.1 Treatment capacity estimation	2.8
2.7 Simulation of the proposed UCT systems	2.9
2.8 Modifications to the existing pilot plants to convert to UCT systems	2.12
2.9 Process control and system calibration	2.13
2.9.1 Influent flow control and measurement	2.13

2.9.2	Dissolved oxygen control and measurement	2.13
2.9.3	Mixed liquor recycle control and measurement	2.13
2.9.4	Waste flow control and measurement	2.14
2.10	Commissioning and operational adjustments to the pilot plants	2.14
2.11	System operating conditions and changes during experimental periods	2.15
2.12	Data acquisition and sample analysis	2.19
2.13	Measured system performance	2.23
2.13.1	Influent data	2.23
2.13.2	Reactor parameters	2.25
2.13.3	Effluent quality	2.34
2.14	Laboratory scale UCT system	2.35
2.14.1	Experimental setup and control	2.35
2.14.2	System performance monitoring	2.36
2.14.3	Experimental results	2.36
2.15	Filament Identifications	2.39
2.16	Conclusions	2.40
2.16.1	Operation problems	2.40
2.16.2	COD removal performance	2.40
2.16.3	Nitrogen removal performance	2.41
2.16.4	Phosphorus removal performance	2.42
2.16.5	Sludge settleability and filament identification	2.44
2.16.6	Simulation of fullscale pilot plants	2.45
2.16.7	Closure	2.46
2.17	References	2.47
3	BULKING CONTROL USING REDOX POTENTIAL: SUMMARY OF DETAILED REPORT Tsai <i>et al.</i> (2002)	3.1
3.1	Motivation	3.1
3.2	Experimental systems and investigation methods	3.1
3.2.1	System set up and operation	3.1
3.2.2	Control of aeration cycle	3.3
3.2.3	Daily sampling and testing of the systems	3.4
3.3	Experimental results and discussion	3.6
3.3.1	System performance - Period 1 (Day 1 to 245)	3.7
3.3.2	System performance - Period 2 (Day 250 to 384)	3.10
3.3.3	System performance - Period 3 (Day 385 to 426)	3.13
3.3.4	System performance - Period 4 (Day 427 to 459)	3.15
3.3.5	System performance - Period 5 (Day 460 to 497)	3.18
3.3.6	System performance - Period 6 (Day 498 to 582)	3.21
3.3.7	System performance - Period 7 (Day 583 to 831)	3.23
3.3.8	System performance - Period 8 (Day 832 to 859)	3.30
3.3.9	System performance - Period 9 (Day 860 to 978)	3.33
3.4	Conclusions	3.35
3.5	References	3.35
4	GLOSSARY OF TERMS	4.1